storing a new state metric of the initial state of the trellis

in a respective initial state register as soon as the

respective initial state of the trellis has been stored in the

buffer register.--

Remarks:

This preliminary amendment is being submitted in an effort to

correct informalities and provide improved translations of

certain wording in the initial application, and to present

claims in proper U.S. claims idiom and to remove multiple

dependencies. The changes are not made for any reason related

to the statutory requirements for a patent nor do they narrow

the scope of the claim for any reason related to the statutory

requirements for a patent. The newly entered claims are fully

supported in the original claims.

The recommended subheadings have been inserted at the proper

locations in the text.

New FIGS. 2 and 4 of the drawings are submitted for approval.

Specifically, functional blocks in FIGS. 2 and 4 have been

given labels.

All of the changes are properly supported in the original

application. No new matter has been added.

An early action on the merits of the application is solicited.

The fee for seven (7) additional claims in excess of twenty (20) pursuant to Section 1.16 in the amount of $126.00 is enclosed herewith. Applicants note that the fee for one additional claim in excess of twenty (20) was already paid.

Please charge any other fees that might be due with respect to Sections 1.16 and 1.17 to the Deposit Account of Lerner and Greenberg, P.A., No. 12-1099.

Respectfully submitted,

Gregory L. Mayback
Reg. No. 40,719

For Applicants
GLM/bh

October 31, 2001

Lerner and Greenberg, P.A.
P.O. Box 2480
Hollywood, Florida 33022-2480
Tel.: (954) 925-1100
Fax: (954) 925-1101

<u>Version of Specification With Markings to Show Changes Made</u>:

Replace the paragraphs beginning on lines 7, 10, and 12 of page 1, with:

--<u>Background of the Invention</u>:

<u>Field of the Invention</u>:

Such an apparatus and such a method are [known from [1]] <u>disclosed in WO 99/34520, corresponding to U.S. Patent NO. 6,115,436 to Ramesh et al. (hereinafter "Ramesh")</u>.

In the method [known from [1]] and [in the] apparatus [known from [1]] <u>disclosed in Ramesh</u>, a received decoded signal is decoded by [means of] an electrical circuit <u>that is disposed</u> [which is arranged] in accordance with a so-called butterfly structure. [This known] <u>The Ramesh</u> procedure is used exclusively for channel decoding of channel-coded signals.--.

Replace the paragraphs beginning on lines 1, 11, 16, 18, and 23 of page 2, with:

--[[2]] <u>W. Koch and A. Baier, Optimum and Suboptimum Detection of Coded Data Disturbed by Time-Varying Intersymbol Interference, IEEE GLOBECOM, pages 1679 - 1684, 1999 (hereinafter "Koch")</u>, discloses the determination of a so-called transition metric for a Viterbi algorithm in the course of equalization of physical signals for so-called soft decision equalization. Furthermore, [[2]] <u>Koch</u> discloses the entire Viterbi method, matched to the appropriate transition

metrics for a so-called butterfly structure of a trellis, and the determination of the "optimum" signal sequence of the received signals by [means of] so-called back-tracing from the optimum trellis determined.

One particular disadvantage of the procedure described in <u>Koch</u> [[2]] is that the circuit described there is suitable only for equalization of received physical signals. The Koch apparatus cannot be used for channel decoding of physical signals.

The principles of the Viterbi algorithm are described in [[3]] <u>G.D. Forney, The Viterbi-Algorithm, Proceedings of the IEEE, Vol., 61, No. 3, pages 268 - 278, 1973</u> (hereinafter "Forney").

<u>Summary of the Invention</u>:
<u>It is accordingly an object of the invention to provide a</u> <u>device and method to carry out a veterbi algorithm that</u> <u>overcomes the hereinafore-mentioned disadvantages of the</u> <u>heretofore-known devices of this general type and that makes</u> [The invention is thus based on the problem of making] it possible to use a Viterbi algorithm flexibly for different, selectable operating modes, for example, for equalization and for decoding received physical signals.--

Replace the paragraphs beginning on page 12, lines 5, 7, 9, 12, 15, 20, and 24 with:

--Brief Description of the Drawings:

[An exemplary embodiment of the invention will be explained in more detail in the following text and is illustrated in the figures, in which:

Figure 1   shows an exemplary embodiment of an electrical
          circuit according to the invention;]

Fig. 1 is a block circuit diagram of an exemplary embodiment of an electrical circuit according to the invention;

[Figure 2 shows a block diagram, illustrating the sending, transmission and reception of an electrical signal;]

Fig. 2 is a block circuit diagram illustrating the sending, transmission, and reception of an electrical signal;

[Figures 3a and 3b show a sketch illustrating a binary trellis according to a butterfly structure for equalization (Figure 3a) and for decoding (Figure 3b) of an electrical signal;]

Fig. 3A is a diagram illustrating a binary trellis according to a butterfly structure for equalization of an electrical signal;

Figs. 3B is a diagram illustrating a binary trellis according to a butterfly structure for decoding an electrical signal; and

[Figure 4 shows a block diagram of an exemplary embodiment of a digital signal processor according to the invention.]
Fig. 4 is a block circuit diagram of an exemplary embodiment of a digital signal processor according to the invention.

Description of the Preferred Embodiments:
Referring now to the figures of the drawings in detail and first, particularly to Fig. 2 thereof, there is shown, [Figure 2 shows,] symbolically, a source 201, from which a message 202 is intended to be transmitted from a transmitter 200 to a sink 221 in a receiver 211.--.

Replace the paragraphs beginning on page 17, line 14, with:
--To simplify understanding of the invention, the rough structure of the Viterbi algorithm will be explained in the following text (see Figure 3A [3a] and Figure 3B [3b]). Details of the Viterbi algorithm are described in Fourny [[3]].--.

FIG 2

Source

Modulation Unit

Transmitter

200

202   204   206

201 → 203 → 205 → 207

Source Coder

Channel Coding Unit

Interference

209

Physical Channel

210 → 208

212

Demodulation Unit

220   218   216   214

221 ← 219 ← 217 ← 215 ← 213

Receiver   211

Sink

Source Decoding Unit

Channel Decoding Unit

Equalization Unit

FIG 4

Electrical Signal

215

401

Processor

403

Memory

404

Viterbi Algorithm

405

Digital Signal Processor

400

211

402

406

Receiver